

# Inspecam® PTA PTIP HD

Pan- Tilt - Zoom Cameras



## FEATURES

- Analogic (PTA) or IP (PTIP)
- Pan 360° free rotation / Tilt 90°
- Ruggy and affordable.
- Programmable functions: Focus, iris, day/night, white balance, etc.

## SPECIFICATIONS

### OPTICAL

Lens  
Zoom  
Focus  
Iris  
Viewing angle in air (Horiz)  
Viewing angle in water (Horiz)  
Movement Range

### ANALOGIC

3.8 - 38 mm  
10x Optical 10x Dig  
Auto / Manual  
Auto / Manual  
51° (wide) - 5.6° (tele)  
40° (wide) - 4.4° (tele)  
Pan 360° (endless) Tilt 90°

### IP

5.1 - 51 mm  
10x Optical 12x Dig  
Auto / Manual / Semi auto  
Adjustable  
54° (Wide) - 4.9° (Tele)  
46° (Wide) - 4.3° (Tele)  
Pan 360° (endless) Tilt 90°

### ELECTRICAL

Horizontal Resolution  
Minimum Illumination  
Day / Night  
White Balance  
Supply

700  
0.7 lux (color) 0.02 lux (BW)  
Auto / Day / Night  
Auto / Manual  
12 V 0.7 A

HD 2000K Pixels  
0.5 Lux (color) 0.001 Lux(BW)  
Auto / Day / Night  
Auto / Manual / Adjustable  
PoE

### MECHANICAL

Housing  
Window  
Diameter  
Length  
Weight in air  
Weight in water

Black POM / Black hard anod. alum. 6082 / Stainless steel 316  
Optical acrylic  
172 mm (POM) 152 mm (Alum) 152 mm (SS)  
220 mm (excl. connector)  
3.8 kg (POM) 4.1 kg (Alum) 9.6 kg (SS)  
2.6 kg 2.9 kg 6.2 kg

### ENVIRONMENTAL

Rated depth  
Operating temperature  
Storage temperature

300 m  
-10°C to 50°C  
-20°C to 70°C