



### Inline Cable Colour Code

- 1 Black
- 2 White
- 3 Green

(Bulkhead Leads Number Tagged)

### Material Specifications

|                      |                                      |
|----------------------|--------------------------------------|
| Connector Body       | : Neoprene (CR)                      |
| Bulkhead Body        | : Brass UNS-C36000                   |
| Contacts             | : Brass UNS-C36000                   |
| Nuts & Washers       | : Brass UNS-C36000                   |
| Location pin         | : AISI 303                           |
| 'O' Rings            | : Nitrile                            |
| Locking Sleeve       | : Delrin                             |
| Snap Ring            | : AISI 302                           |
| Inline Cable (60 cm) | : 16 AWG 1,34 mm <sup>2</sup> Rubber |
| BH Leads (30 cm)     | : 18 AWG 1,0 mm <sup>2</sup> Teflon  |
| Options              | : See index pages                    |

### Connector Specifications

|                           |                                  |
|---------------------------|----------------------------------|
| Single Contact Rating     | : 600 V @ 15 Amp                 |
| Connector Rating 2-3 pins | : 600 V @ 10 Amp                 |
| Insulation Resistance     | : >200 megaohm                   |
| Contact Resistance        | : <0,01 ohm                      |
| Wet Matings               | : >500                           |
| Temp. Rating              | : -4° to +60° C<br>25° to 140° F |
| Depth Rating              | : 1.400 bar - 20.000 psi         |

Dimensions in mm.  
Threads in inches.  
1 inch = 25,4 mm.  
1 mm = 0,03937 inch.

Modification rights reserved

Drawing No.  
SE 300-2